



浙江万马天屹通信线缆有限公司

Zhejiang Wanma Tianyi Communication Wire & Cable Co., Ltd.

RG6+Power Cord

Description

	Material	Diameter (mm)
Inner Conductor	CCS	1.02
Dielectric	Foamed PE	4.57
Al Foil	Bonded APA	4.78
Overall Braid	Al-Mg	
Inner Conductor	CCA/CU	7*0.37
Dielectric	PE	1.75
Jacket	PVC	6.93



Characteristics

Capacitance	52 pF/m	SRL 5~1000MHz	18dB Min.
Velocity	82%	Impedance	75 ± 3 ohms

Attenuation @ 20°C

MHz	dB/100ft	dB/100m.	MHz	dB/100ft	dB/100m.
55	1.60	5.25	450	4.40	14.43
211	3.05	10.00	500	4.66	15.29
250	3.30	10.82	550	4.90	16.08
270	3.37	11.04	600	5.10	16.73
300	3.55	11.64	750	5.65	18.54
330	3.74	12.26	870	6.11	20.04
350	3.85	12.63	1000	6.55	21.49
400	4.15	13.61			



Tianyi Industrial Area, Faihuyuan Town, Lin'an City, Zhejiang 311300, China

Tel: +86 571 2361 6526 Fax: +86 571 6375 1363

www.wanmatianyi.com